



Cam Spray Trailer Mounted Sewer and Drain Jetters

Cam Spray's STB2712H, STB3708H, STB4007H and STB2511D are the most popular Trailer Mounted Sewer and Drain Jetters Cam Spray builds. The gasoline powered models use a 27 h.p. Honda Engine and the Diesel powered model uses a Hatz Diesel Engine.

The Standard Features of the STB2712H, STB3708H, STB4007H include a five gallon fuel tank, low oil shutdown, keyed ignition switch with electric start, choke lever, hour meter, fuel filter, fuel pump while the diesel engine driven STB2511D Hatz Diesel model features electric start. An Industrial Triplex Plunger Pump with stainless steel valves, ceramic plungers and a power pulse valve to help blast away tough clogs and navigate longer runs with 90 and 45 degree elbows. The water inlet includes a shut off valve, 1 1/4" rigid inlet hose and a high volume water filter. An Air purge Valve on the pump is available to blow all of the water out of the complete system from pump inlet to hose discharge to help protect the system from freezing conditions.

The trailer is heavily constructed with steel tube box frame, full diamond plate deck, retractable tongue, electric brakes, DOT rated 5000# axle, road ready lights and wiring, powder coated finish, 15" Chrome Wheels and 6 bolt hubs.

A 300 gallon water tank can be filled with the 2" hydrant fill, or hose fill with the 150' garden hose on the hand crank reel. Cam Spray recommends the tank be filled while on location. If your application requires you to transport water on roadways we would advise adding baffles to the tank. Contact Cam Spray for information on baffles for this model.

The water tank system features a drain and a float switch to shut down the system should the tank run out of water.

The Cam Spray STB2712H, STB3708H, STB4007H and STB2511D Sewer and Drain Jetters have controls located on the rear of the trailer in the area where most of your work is done. A large pressure gauge allows monitoring the system pressure, a high pressure water valve controls water flow, and a remote throttle control governs the speed of the engine.

The 12 Volt DC powered reel holds Jetter Hose and features a 2:1 drive system with a locking pin on the reel. The reel allows for free spooling of the hose while going into the drain and powered assist when retracting the hose from the drain and returning the hose for storage on the reel. The reel is activated by a push button switch on the reel motor or can be activated by using the foot switch.

A retractable hose guide on the back of the trailer aids in guiding the hose into the drain or sewer line. For cold weather operation Cam Spray has made recirculation of the water easy. By simply removing the nozzle from the jet hose, attach the quick coupler plug and connect the hose to the recirculation coupler on the top of the tank. Turn the water shut-off valve back on and the water will continue to circulate keeping the system from freezing. Be sure to adjust engine speed to keep water flowing adequately as low flow and colder temps can still set up a water freezing condition.

The Cam Spray STB2712H, STB3708H, STB4007H and STB2511D Sewer and Drain Jetters standard equipment includes a 4 nozzle set (laser, degreaser/deicer, monster mole and flusher/ram) a storage box and a tip cleaner, a tiger tail to protect your hose when entering the drain line, safety shield, rubber gloves, a high visibility safety vest, strobe light with 5' extension pole and a bank of three 12V DC power ports located in the tool box for the strobe and other accessories. Remember to use adequate safety gear and extreme caution while operating machinery.

When you are finished with the job wash down the area with the 50' wash down hose and trigger gun included with the machine.

All of your valuable accessories can be stored in the lockable tool box located on the rear of the trailer.

7-11 1/2 gallons
per minute

RJM

800-620-4773
www.rjmcompany.com



Cam Spray Trailer Mounted Sewer and Drain Jetters




STB2712H

7-11 1/2 gallons per minute



STB2712H Pump and Engine



STB2712H, Powered Reel, Hydrant Fill, 300 gallon tank, 150' tank fill hose on manual reel, Locking Tool Boxes.

Model	PSI	GPM	H.P.	Engine	Jet Hose Dimensions	Reel Type	Water Tank Capacity	Dimensions L x W x H	Dry Weight
STB2712H	2700	11.5	27	Honda	400' x 1/2"	Powered	300 gallon	156" x 72" x 64"	1860 lbs.
STB3708H	3700	8	27	Honda	300' x 3/8"	Powered	300 gallon	156" x 72" x 64"	1860 lbs.
STB4007H	4000	7	27	Honda	300' x 3/8"	Powered	300 gallon	156" x 72" x 64"	1860 lbs.
STB2511D	2500	11.5	20	Hatz Diesel	400' x 1/2"	Powered	300 gallon	156" x 72" x 64"	1910 lbs.



800-620-4773
www.rjmcompany.com