

The Marquise Model JMAXX®

Frame

The Marquise's frame consists of a uni-body construction which allows the motor, head bearing, and reel shaft assemblies to be bolted directly to the frame.

Electrical Wiring

The Marquise's electrical wiring is located in the conduit box on the right side of the motor, housing both the forward/reverse switch and the air foot switch. The Ground Fault Circuit Interrupter (GFCI) is built into the electrical cord for added safety.

The air foot switch is standard equipment on The Marquise. This switch allows the operator to turn the machine on and off while the hands stay on the cable.

RPM/Drive

The Marquise has a 1/3 HP motor and operates at 200 rpm's. The heavy-duty, self-aligning head bearing for The Marquise has a cast housing which reduces stress and prevents premature wear.

Maneuverability

The Marquise can have 6" wheels and a detachable "T" handle added.

Cable and Reel Selections

The Marquise was designed to handle several reel sizes. The reel selected is set in place and slipped onto the reel shaft. Drive lugs are mounted on the drive plate and slip through the openings in the back of the reel. The reel is held in place by the revolving arm.

Standard Package

The Marquise's standard package comes with the following items: revolving arm; 1/3 HP motor at 200 rpm; 19" open metal spoke reel; 1/2" x 75' cable; reel attachment; and choice of cable end fittings. (Wheels and handle are not standard.)

See the machine packages and accessories chart on the next page for additional options.



As shown at left with D1S reel, a D8SL9A arm with a 31020 arm extension, a stubbed GFCI cord, and a mobility kit. (See options on the next page.)



As shown above with D1SE reel, a D8SL9A arm with a 31020 arm extension, a stubbed GFCI cord, and a mobility kit. (See options on the next page.)

Machine Specifications (specs are approximate)

Length

Machine only 26"
With handle and wheels 44"

Width

Machine only 13"
With wheels and handle 17-1/2"

Height

Machine (with or without wheels & handle) 17"

Weight

Base Machine with 15.1 lb. 1/3 HP motor 44.5 lbs.
Machine with wheels & handle 56.5 lbs.
Narrow Wheels 13 lbs.
14" Open Metal Spoke Reel 8.5 lbs.
14" Enclosed Metal Spoke Reel 10.5 lbs.
16" Open Metal Spoke Reel 9.5 lbs.
16" Enclosed Metal Spoke Reel 11.5 lbs.
19" Open Metal Spoke Reel 10.5 lbs.
19" Enclosed Metal Spoke Reel 16.5 lbs.

Line Size 1-1/4" - 4"

Recommended Use: residential lines, roof vents, sinks, bath tubs, shower drains, and laundry drains.



REELS			REEL ATTACHMENTS	FLOATING RINGS	FLOATING RING ATTACHMENTS	REVOLVING ARM	CABLES*	
Part #	Dimensions	Description	Part #	Part #	Part #	Part #	Part #	Dimensions
D1L	14" dia., 9" h	Open Metal Spoke Reel	D3L	None	None	D8SL2A with 31021 Arm Extension	__25-075 __31-060 __38-060	1/4" up to 75' 5/16" up to 60' 3/8" up to 60'
D1LE	14" dia., 8" h	Enclosed Metal Spoke Reel	D3S	None	None	D8SL2A with 31021 Arm Extension	__25-075 __31-060 __38-060	1/4" up to 75' 5/16" up to 60' 3/8" up to 60'
15ERP	15" dia., 8" h	Enclosed Polycarbonate Reel	None	None	None	D8SL2A with 31021 Arm Extension	__25-075 __31-060 __38-060	1/4" up to 75' 5/16" up to 60' 3/8" up to 60'
D1S	16" dia., 9" h	Open Metal Spoke Reel (Standard)	D3L	D2JS	D3E	D8SL2A with 31021 Arm Extension	__25-100 __31-090 __38-090 __50-075	1/4" up to 100' 5/16" up to 90' 3/8" up to 90' 1/2" up to 75'
D1SE	16" dia., 8.5" h	Enclosed Metal Spoke Reel	D3S	D2JS	D3E	D8SL2A with 31021 Arm Extension	__25-100 __31-090 __38-090 __50-075	1/4" up to 100' 5/16" up to 90' 3/8" up to 90' 1/2" up to 75'
D1S1	19" dia., 8.5" h	Open Metal Spoke Reel	D3L	D2JM D2JR	D3E D3R (male end) D3RJ (slip joint)	D8SL9A with 31020 Arm Extension	__50-090 __62-080 __69-080	1/2" up to 90' 5/8" up to 80' 11/16" up to 80'
D1S1E	19" dia., 8.5" h	Enclosed Metal Spoke Reel	D3S	D2JM D2JR	D3E D3R (male end) D3RJ (slip joint)	D8SL9A with 31020 Arm Extension	__50-090 __62-080 __69-080	1/2" up to 90' 5/8" up to 80' 11/16" up to 80'

MACHINE PACKAGES & ACCESSORIES	
Part #	Description
D3113200	1/3 HP Motor at 200 rpm
JMaxxSP	1/3 HP Motor at 200 rpm without PCFR and with D1S reel
JMaxxSPE	1/3 HP Motor at 200 rpm without PCFR and with D1SE reel
JMaxxSPA	1/3 HP Motor at 200 rpm without PCFR and with D1S1 reel
JMaxxSPEA	1/3 HP Motor at 200 rpm without PCFR and with D1S1E reel
31005	1/3 HP Motor
31001	Mobility Kit (wheels & handle)
DRC14	Reel Cover for 14" Open Reel
DRC16	Reel Cover for 16" Open Reel
DRC19	Reel Cover for 19" Open Reel

* Add **CH** in front of cable part # for Hollow Core
& Add **LW** after part # if you want it to be Loose Wound

* Add **CI** in front of cable part # for Inner Core
& Add **LW** after part # if you want it to be Loose Wound

* Add **CC** in front of cable part # for Cable-in-Cable (3/4" x 50' or 3/4" x 100' and 11/16" x 50' or 11/16" x 100')

* Add **OH** in front of cable part # for Oil Tempered Hollow Core (11/16" and 3/4" only)

* Maximum length of cable is not always the recommended length. Custom lengths are available.

