

# K-40 MACHINE K-39 MACHINE

RJM Company  
800-620-4773  
brianmoss@rjmcompany.com  
www.rjmcompany.com

## K-40

### K-40 Machine

The K-40 sink machine is ideal for cleaning small secondary drain lines from 3/4" to 2-1/2" lines. The K-40 sits flat on the floor or counter top and also tips onto its back for easy access to sink drains and bathtubs full of water. The K-40 practically eliminates job site clean-up thanks to the patented guide hose auto feed accessory that completely contains the rotating cable and eliminates any waste water splashing or spraying. The K-40 is CSA approved and approved to UL standards (NRTLCL).

### RPM/Drive

A 1/8 HP induction motor quietly delivers enough torque to clear even the toughest blockages.

### Cable and Reel Selections

The two-piece "twist lock" reel housing will not dent or corrode and allows easy access to the inner reel and cable. The special inner reel design virtually eliminates cable flip-over and reel leakage.

The auto feed unit automatically advances and retrieves the cable making the job faster, cleaner and easier. The K-40 includes an exclusive speed bump cable, featuring a cable end indicator to limit cable damage.

### Standard Package

The standard K-40 machine package (*part number R71722*) comes with an auto feed, guide hose, mounting bracket, speed bump, and 5/16" x 35' cable.

Another K-40 machine package (*part number R71702*), comes with 5/16" x 25' cable.

A third option is the K-40 package (*part number R71712*), comes with an auto feed and 5/16" x 35' cable.



Shown above is the K-40 Machine.

## K-39

### K-39 Machine

The K-39 sink machine is excellent for small line cleaning. It opens clogged lavatory, sink lines, urinals, and the bathtubs and shower drains. It is available in two styles - manual and auto feed. Both have the slide action chuck for quick locking and releasing of the cable. An advanced two-way feed keeps hands off the cable by using the push of a lever to advance and retrieve the cable. It is lightweight, easy-to-use, and no set up is required.

### RPM/Drive

The variable speed power unit rotates the cable from 0 to 450 rpm. It is CSA approved. The K-39 is available in two styles: manual and auto feed. Both styles have slide action chuck for quick locking and releasing of the cable. The advanced two-way feed keeps hands off the cable - advancing and retrieving cable with the push of a lever.

### Cable and Reel Selections

The K-39 has a two piece twist lock canister with an interchangeable inner reel. This makes cable change out simple and easy to match the right cable to the job. The inner reel prevents water leaks and greatly reduces cable flip over. The reels will not rust or dent. The reel capacity is 50 feet for 5/16" cable or 35 feet of 3/8" cable.

### Standard Package

The standard K-39AF machine package (*part number R21888*) comes with a slide action chuck, auto feed, and 25 feet of 5/16" cable. The K-39 machine package (*part number R68057*) comes with the slide action chuck and 25 feet of 5/16" cable.



Shown above is the K-39AF Machine, part number R21888.



Shown above is the K-39 Machine, part number R68057.