


Gorlitz's cable feeder mounting bracket is required to install our power cable feeder and pullers. Power feeder bracket T 02 is required for GO 50 thru GO 68HD series machines and T 02A is required for GO 50 series machines.



Gorlitz's loading ramps are designed for simple loading or unloading of our GO 68 (T 04) and GO 62 (T 04A) Series sewer cleaning machines. Our ramps are equipped with a fold down section, wheel stops and mounting hardware. The ramps are painted in black and weigh approximately 57 lbs for model T 04 or 49 lbs for model T 04A. T 04 Overall dimensions with fold down section in upright position are 50" L X 23" W X 20" H. T 04A Dimensions are 42" L X 23" W X 20" H.



Gorlitz's winch installation kit is provided with a powerful 1500 lbs. full capacity 12 Volt DC motor, a 40 amp 12 Volt fuse, wire harness, forward/reverse switch and manual crank emergency handle.



Gorlitz's optional pneumatic foot switch is supplied with a standard 6 foot air hose that replaces the electric on/off switch control on our GO 50, GO 62 and GO 68 (series) sewer and drain cleaning models. It allows the operator's hands to be free and provides more flexibility while operating the equipment.



Gorlitz's electric foot switch allows the operator's hands to be free to guide the cable while controlling the on/off position of the machine. This unit is made from a heavy duty metal casting and painted in a bright fluorescent color for easy visibility.



Gorlitz's toilet augers are available in 3 or 6 foot lengths with bulbhead or downhead attachments. Our auger T 08 comes with 3 foot long flexible hollow core cable specially designed for water-saver toilets, while augers T 10 and T 11 are available only with inner core cables.

|           |           |           |
|-----------|-----------|-----------|
| Bulb Head | Down Head | Down Head |
| T 10B 3'  | T 10 3'   | T 08 3'   |
| T 11B 6'  | T 11 6'   |           |



Gorlitz's specially designed 6" diameter ball type extra heavy duty force cup plunger, with a reinforced ribbed construction, is supplied with a 20" long wooded handle. The plumbers choice.



Gorlitz's hydro-thrust plunger is a large capacity funnel shaped cup that acts as a super-charger against hard to move stoppages in even oddly shaped toilet bowls. The funnel can be retracted and used in flat sinks and tubs.

Gorlitz's tile probes are used to locate buried sewer or drain pipes. Models T 14 and T 15 are made of durable 1/2" diameter solid steel rod. Models T 15B and T 15C are constructed from 1/2" diameter hollow core rod and include a brass hose connection and shut-off valve to control water flow. Probes are powder coated and provided with molded rubber grips for added comfort and are available in different lengths.



T 14 40"                      T 15B 48"  
T 15 48"                      T 15C 60"

Gorlitz's all purpose gloves are made of a strong, durable canvas. The fingers are composed of a single layer of soft swede leather while the index finger, thumb and palm have a double layer. One size fits all.



T 16

Gorlitz's "ugly" gloves are constructed out of a tough PVC material. The palm is molded with small PVC particles to prevent the operators gloves from twisting or snagging. The gloves themselves are acid and oil resistant, flexible, and keep your hands clean and dry. Available in wrist or forearm length.



T 17 Regular

T 17A Long

Gorlitz's digging bars are helpful tools in aiding the prying or lifting of various cover plates. Constructed out of 7/8" hex material, one side is provided with a chisel shaped end while the other features a sharp point.



T 18 5'                      T 19 6'

Gorlitz's pressure bags use water pressure supplied from a garden hose to blast open clogged sewer or drain lines. Constructed out of canvas and provided with brass fittings, they are an indispensable item. Available in 5 different sizes.



T 20 1 1/2"                      T 22 3"                      T 24 6"  
T 21 2"                      T 23 4"

Gorlitz's vent roller is used to help guide the cable smoothly down the vent pipe and prevents damage to the pipe edge.



T 25

Gorlitz's bolt cutters are used in cutting and repairing broken or damaged cables. Cutting blades are constructed from solid hardened tool steel for extra longevity. Available in 2 sizes.




T 26 24"                      T 26 30"

Gorlitz's center punch is designed to displace any sharp edges and/or spread the first coil of any cable for easy installation of our cable ends and connectors. Our center punch is heat treated for longer life.



T 27

Gorlitz's splash guards are constructed from nylon reinforced plastic coated canvas. They are recommended for our open reel models to prevent water from splashing onto any nearby surroundings. Models T 28 and T 28S fold together for convenient storage. Models T 28A thru T 28D are provided with rubber bands at each diameter opening for a snug fit on the reel.



T 28A 3/8"  
T 28B 1/2"  
T 28C 5/8"  
T 28D 11/16"

T 28  
T 28S