

NEW & Prepared to Work!



THE PIVOT (DM150)

Removable lifting handle is optional and is ideal for carrying the reel separate from the frame.

RJM Company
800-620-4773
brianmoss@rjmcompany.com
www.rjmcompany.com

1/3 HP rectified DC gear motor at 230 rpm.

A guide tube and quick-lock guide tube bracket are options for the 5/16" & 3/8" cable.

Heavy-duty self-aligning head bearing increases the life span of the reel.

Five notched positions allow the machine to pivot from 0-90 degrees.

A continuously welded uni-body frame for strength & durability.

Pocket molded hand grip for easy carrying.

Switch guard that protects the forward/reverse switch from accidentally going into reverse.

Runs 5/16", 3/8" & 1/2" cable.

Coming soon is an optional kit with pulling handle, axle brackets & wheels, & optional machine cart.

Loosen the quick release "T" handles for easy reel removal.

Air foot pedal comes standard allowing the operator to turn the machine on and off while the hands stay on the cable.

Duracable® Machines

Ends

ProClean® Drain Care

Blades

DuraFlex® Cable

NEW & Prepared to Work!



THE PIVOT (DM150)

REELS			REEL ATTACHMENTS	FLOATING RINGS	FLOATING RING ATTACHMENTS	REVOLVING ARM	CABLES*	
Part #	Dimensions	Description	Part #	Part #	Part #	Part #	Part #	Dimensions
14PRK	14" diameter	Enclosed Polyethylene Reel with inner reel and <u>Head Bearing</u>	N/A	N/A	N/A	38RA	__31-090 __38-090	5/16" up to 90' 3/8" up to 90'
14PROK	14" diameter	Enclosed Polyethylene Reel, oversized, with inner reel and <u>Head Bearing (Standard)</u>	N/A	N/A	N/A	50RA	__31-090 __38-090 __50-090	5/16" up to 90' 3/8" up to 90' 1/2" up to 90' ^

MACHINE PACKAGES				
Part #	Horse Power	RPM	Reel	Cable
DM150A	1/3 HP Motor	230 rpm	14PROK	1/2" x 75'
DM150A1	1/3 HP Motor	230 rpm	14PRK	3/8" x 75'
DM150A2	1/3 HP Motor	230 rpm	two 14PROK's & one 14PRK	1/2" x 75' and 3/8" x 75'

MACHINE ACCESSORIES/ REPLACEMENT PARTS	
Part #	Description
52005	1/3 HP gear-driven motor
25074	Air Foot Pedal (rubber) with 10' tubing
25061	Air Switch with Strain Relief Nut
52025	Lifting Handle with Grip
52024	Lifting Handle Bracket
25216	Guide Tube
11036	Quick-Lock Guide Tube Bracket
14PR	14" Polyethylene Reel with Inner Reel (no head bearing)
14PRO	14" Polyethylene Reel, oversized, w/ Inner Reel (no head bearing)
DM52040	Machine Cart, optional

Standard Package

The Pivot's standard package (part number DM150A) comes with the following: revolving arm, 1/3 HP motor at 230 rpm, 14" enclosed polyethylene reel, oversized, with head bearing, 1/2" x 4' tail piece, 1/2" x 75' cable, and choice of end fittings.

Machine Specifications (specs are approximates)

Length	
Standard Machine	17"
Width	
Standard Machine	20"
Height	
Machine with 14PRK reel	16"
Machine with 14PROK reel	16"
Weight	
Machine with 1/3 HP Motor	34 lbs.
14PR Reel with inner reel	6.5 lbs.
14PRK Reel with inner reel and head bearing	7.75 lbs.
14PRO Reel and inner reel	7 lbs.
14PROK Reel with inner reel and head bearing	8.25 lbs.
Line Size	1-1/4"-4"

Recommended Use: residential lines, sinks, bathtubs, shower drains, roof vents and floor drains.

- * Add **CH** in front of cable part # for Hollow Core.
- * Add **CI** in front of cable part # for Inner Core.
- * Maximum length of cable is not always the recommended length.
- * Custom lengths are available.
- * See pages 54-57 for more detailed cable information.
- ^ A 1/2" x 4' tail piece (part number TS50-004) is standard with the 14PROK reel.



RJM Company
800-620-4773
brianmoss@rjmcompany.com
www.rjmcompany.com