



JETTER NOZZLES

Gorlitz's standard nozzles, available in brass or stainless steel, are recognized for their precision machining and short overall length to accomplish tight turns. Precise jets and smooth orifices offer rapid forward movement and superior cleaning power.




JN 01	1/8" 2-3 GPM	JN 01B	1/8" 2-3 GPM
JN 11	1/4" 2-4 GPM	JN 11B	1/4" 2-4 GPM
JN 21	3/8" 4-6 GPM		

Gorlitz's thrust head nozzles are equipped only with rear jets for maximum forward propulsion. Suggested for general applications.



JN 22	3/8" 4-6 GPM
JN 32	1/2" 8-10 GPM



JN 03	1/8" 2-3 GPM	JN 03B	1/8" 2-3 GPM
JN 13	1/4" 2-4 GPM	JN 13B	1/4" 2-4 GPM
JN 23	3/8" 4-6 GPM		
JN 33	1/2" 8-10 GPM		




JN 24	3/8" 4-6 GPM	JN 04B	1/8" 2-3 GPM
		JN 14B	1/4" 2-4 GPM

Gorlitz's laser tip nozzles are manufactured with three or more rear jets and one jet pointing forward to help cut through ice, sludge, grease, etc.




JN 25	3/8" 4-6 GPM
JN 35	1/2" 8-10 GPM




JN 06	1/8" 2-3 GPM	JN 06B	1/8" 2-3 GPM
JN 16	1/4" 2-4 GPM	JN 16B	1/4" 2-4 GPM
JN 26	3/8" 4-6 GPM		
JN 36	1/2" 8-10 GPM		

Gorlitz's corner head nozzles are provided with two rear jets for propulsion and one side jet to assist in making difficult turns.




JN 07	1/8" 2-3 GPM	JN 07B	1/8" 2-3 GPM
JN 17	1/4" 2-4 GPM	JN 17B	1/4" 2-4 GPM



JN 08	1/8" 2-3 GPM	JN 08B	1/8" 2-3 GPM
JN 18	1/4" 2-4 GPM	JN 18B	1/4" 2-4 GPM

Gorlitz's drop head nozzles are highly recommended to negotiate back to back drains or sharp turns.



JN 09	1/8" 2-3 GPM	JN 09B	1/8" 2-3 GPM
JN 19	1/4" 2-4 GPM	JN 19B	1/4" 2-4 GPM



Flex Corner Nozzle
4 Rear Jets

JN 29	3/8" 4-6 GPM
JN 39	1/2" 8-10 GPM

Gorlitz's flex corner nozzles were designed for 3/8" and larger diameter jetting hoses. The flexible 8" long spring section including bulb is replaceable. Suggested applications include difficult turns or sharp bends.



Flex Replacement
Tip

JN 29A	3/8"
JN 39A	1/2"

Note: Nozzles made from brass (identified by the letter "B") should not exceed 2000 psi. Nozzles made from stainless steel should not exceed 4000 psi of working pressure unless specified otherwise. Speciality nozzles are available. Please inquire.

BALL NOZZLES

oversized ball (1.0" Diameter) shape gives added weight to negotiate bends, turns and back to back drains. Available in brass.



Gorlitz's ball head nozzles JB 01 and JB 03 are machined with three or six rear jets for maximum forward propulsion. JB 04 and JB 06 laser tip ball nozzles are machined with three or six rear jets and one jet pointing forward to help cut through ice, sludge, grease, etc.

- JB 01 1/8" 2-3 GPM (3)
- JB 03 1/8" 2-3 GPM (6)
- JB 04 1/8" 2-3 GPM (3/1)
- JB 06 1/8" 2-3 GPM (6/1)

JETTER TOOLS & ACCESSORIES

Gorlitz's adjustable in-line liquid injectors are made from brass and stainless steel components. Injectors are provided with 3/8" quick disconnect fittings and 1/4" hose barb. Maximum operating temperature is 180° F and 3000 psi of pressure.



- JT 100 2-3 GPM
- JT 101 3-5 GPM

Gorlitz's liquid strainer assembly includes 8 feet of 1/4" diameter clear hose. The strainer is made from high impact reinforced nylon and supplied with 1/8" to 1/4" hose barb.



- JT 102

Gorlitz's 4000 psi heavy duty trigger gun assembly includes a 36" lance with molded grip. The spray tip incorporates an adjustable high/low variable fan nozzle. The handle is contoured to provide comfort, safety and smooth trigger action. Fittings are 3/8" npt inlet and 1/4" outlet.



- JT 103

Gorlitz's constant speed turbo nozzle will produce up to 3500 psi of cleaning power. Applications include removal of paint, rust, scale, algae and graffiti.



- JT 104

Gorlitz's super flexible premium grade PVC gloves offer an excellent wet/dry grip and are also used to handle acids and caustics. They are abrasion resistant and suited best to handle oily, greasy materials. Treated with antibacterial agents actifresh.



- JT 105

Gorlitz's nozzle cleaning kit contains an assortment of specially designed and tempered wire files to clean most any nozzles orifices.



- JT 106

Gorlitz's low pressure garden hose shutoff valve simplifies the water on/off procedure. Provided with standard 3/4" garden hose fitting.



- JT 107