

FlexiTrace Technical Specification

Description FlexiTrace - Traceable rod assembly.

Part No. 10/TRACE (followed by variant suffix).

Physical

Construction Glass fibre rod and wire conductors in a polypropylene sleeve on plastic coated steel spool.

Rod Length 30, 50, 65, or 80 m.

Rod Diameter 5 mm (0.2 in.).


Transmitting End Diameter 8 mm (0.3 in.).

Minimum Bend Radius 25 cm (10 in.).

Shipping Box Size 50 x 46 x 21 cm (19.7 x 18.1 x 8.3 in.).

Weight 6 kg (13.2 lb).

Shipping Weight 7 kg (15.4 lb).



Operating Frequency Any Radiodetection Transmitter output frequency.

Signal Dependent on the Transmitter used.

Depth Range Down to 3 m (10 ft), dependent on the Transmitter setting.

Operating Temperature Range -20°C to +50°C (-4°F to +122°F).

Miscellaneous

Compatibility Recommended Radiodetection Transmitters: Any Radiodetection Transmitter.

Quality Control BS5750/ISO 9001/EN29001.

Warranty 12 months.



Radiodetection

Radiodetection Ltd
Western Drive
Bristol BS14 OAZ, UK
Tel: +44 (0) 117 976 7776
Fax: +44 (0) 117 976 7775
email:sales.uk@radiodetection.com
<http://www.radiodetection.com>



Radiodetection

Radiodetection products are under continuous development and are subject to change without notice
All rights reserved

TS054EN0