



Cam Spray Trailer Mounted Sewer and Drain Jetters

The STS4018D brings together all the elements of versatility, mobility and power into a sewer and drain jetter. The STS4018D uses a 66 horsepower Kubota 4 cylinder liquid cooled diesel engine that meets the latest EPA tier 4 standards and includes electric start, 2 speed electric speed control, hour meter, an over center clutch for engaging the pump drive system and a lockable engine shroud. Producing 18 gallons per minute at 4000 psi, the industrial five plunger pump has stainless valves and ceramic plungers. This package gives you the power for clearing up to 24" sewer and drain lines.

Standard features include a manually operated power pulse valve for that extra push when you need it. Large volume inlet water filter, water shut off and rigid inlet hose feed. An Air purge valve and a 10 gallon anti-freeze tank gives you several ways to protect the pump and discharge plumbing from freezing conditions. A 25 gallon fuel tank gives you hours of run time on a single fill.

The trailer is heavily constructed with steel tube box frame, full diamond plate deck, electric brakes, DOT rated 7000# axle, road ready lights and wiring, strobe light, powder coated finish, 2 and 5/16" ball hitch, hand crank jack stand, 15" Chrome Wheels and 6 bolt hubs.

The STS4018D uses a 325 gallon tank can be filled with the 2" hydrant fill, also has garden hose adapter fill on the tank. Cam Spray recommends the tank be filled while on location. If your application requires you to transport water on roadways we would advise adding baffles to the tank. Contact Cam Spray for information on baffles for this model.

The hydraulic powered jet hose reel is mounted on a multi position swivel base for operator convenience of positioning the hose guide over the line and features in and out control with a simple lever. All of your controls including the engine key start, two speed engine throttle control, large pressure gauge, and high pressure water valve are located on the rear of the trailer as well, where most of your work is done.

For cold weather operation Cam Spray has made recirculation of the water easy. By simply removing the nozzle from the jet hose, attach the quick coupler plug and connect the hose to the recirculation coupler on the top of the tank. Turn the water shut-off valve back on and the water will continue to circulate keeping the system from freezing. Be sure to adjust engine speed to keep water flowing adequately as low flow and colder temps can still set up a water freezing condition.

Standard accessories include a 4 nozzle set (laser, degreaser/deicer, monster mole and flusher/ram) a storage box and a tip cleaner, a tiger tail to protect your hose when entering the drain line, safety shield, rubber gloves, a high visibility safety vest and strobe light. Remember to use adequate safety gear and extreme caution while operating machinery.

When you are finished with the job wash down the area with the 50' wash down hose and trigger gun included.


All of your valuable equipment can be stored in the locking tongue mount tool box on the front the trailer. Optional equipment includes a Rotating Nozzle for pipe finishing, Root Rat and Warhog root cutting nozzles and the DS200 reel cart with 200' x 3/8" hose or the 526488.J hand carry reel with 100' X 1/4" hose for remote jetting.

Don't see exactly what you want. Look at page 11 & 12 for examples of some of the custom equipment we have built for others.

18 gallons per minute



Cam Spray Trailer Mounted Sewer and Drain Jetters



STS4018D Backside

18 gallons per minute

Model	PSI	GPM	H.P.	Engine	Jet Hose Dimensions	Reel Type	Water Tank Capacity	Dimensions L x W x H	Dry Weight
STS4018D	4000	18	66	Kubota Liquid Cooled Diesel	500' x 1/2"	Hydraulic Powered	325 gallon	177" x 96" x 63"	3200 lbs.



800-620-4773
www.rjmcompany.com