

Everyone's NEW Favorite!



THE EARL (DM125)

Built-in carrying handle.

Pocket molded hand grip for easy carrying.

Loosen the quick release "T" handles for easy reel removal.

1/6 HP induction motor at 230 rpm.

This machine can be run in the upright position & will not tip over.

Standard quick-lock guide tube bracket for easy removal of the guide tube.

The guide tube holder is welded onto the frame and keeps the guide tube secure when not in use.

Reel comes with an inner reel, revolving arm and head bearing.

Heavy-duty, casted, self-aligning head bearing increases the life span of the reel.

Runs 1/4" cable.

Switch guard that protects the forward/reverse switch from accidentally going into reverse.

Air foot pedal comes standard allowing the operator to turn the machine on and off while the hands stay on the cable.

RJM Company
800-620-4773
360-828-5732
brianmoss@rjmcompany.com
www.rjmcompany.com

Duracable® Machines

Ends

ProClean® Drain Care

Blades

DuraFlex® Cable

Everyone's NEW Favorite!



THE EARL (DM125)

REELS			REEL ATTACHMENTS	FLOATING RINGS	FLOATING RING ATTACHMENTS	REVOLVING ARM	CABLES*	
Part #	Dimensions	Description	Part #	Part #	Part #	Part #	Part #	Dimensions
8PRK	8" diameter	Enclosed Polyethylene Reel with inner reel and Head Bearing	N/A	N/A	N/A	25RA	_25-037	1/4" up to 37'

MACHINE PACKAGES				
Part #	Horse Power	RPM	Pedal/Switch	Reel
DM125A	1/6 HP Motor	230 rpm	air foot pedal	8PRK
DM125B	1/6 HP Motor	230 rpm	toggle on/off switch	8PRK
DM125C	1/6 HP Motor	300 rpm	air foot pedal	8PRK
DM125D	1/6 HP Motor	300 rpm	toggle on/off switch	8PRK

MACHINE ACCESSORIES/ REPLACEMENT PARTS	
Part #	Description
11006	1/6 HP Motor
25001	Toggle on/off switch
25074	Air Foot Pedal (rubber) with 10' tubing
25061	Air Switch with Strain Relief Nut
25003	Forward/Reverse Switch
25216	Guide Tube
11036	Quick-Lock Guide Tube Bracket
8PR	8" Enclosed Polyethylene Reel (no head bearing)

Standard Package

The Earl's standard package (part number DM125A) comes with the following items: revolving arm, 1/6 HP motor at 230 rpm, 8" enclosed polyethylene reel, 1/4" x 37' cable, guide tube, and quick-lock guide tube bracket.

Machine Specifications (specs are approximates)

Length	
Standard Machine	20"
Width	
Machine with 8PRK reel.....	10"
Height	
Machine with 8PRK reel	14"
Weight	
Machine with 1/6 HP Motor.....	22.5 lbs.
8PR Reel with inner reel	5 lbs.
8PRK Reel with inner reel and head bearing	6.25 lbs.
Line Size	1-1/4"-2"

Recommended Use: residential lines, sinks, bathtubs, and shower drains.

- * Add CH in front of cable part # for Hollow Core.
- * Add CI in front of cable part # for Inner Core.
- * Maximum length of cable is not always the recommended length.
- * Custom lengths are available.

RJM Company
800-620-4773
brianmoss@rjmcompany.com
www.rjmcompany.com



Duracable® Machines

Ends

ProClean® Drain Care

Blades

DuraFlex® Cable