


DuraSCOPE™

WIFI CAMERA REELS



RJM Equipment Sales
360-828-5732
sales@rjmcompany.com

//////////////////// Proudly Designed and Manufactured in North America //////////////////////



Mini Wi-Fi Reel



Mid Wi-Fi Reel



Large Wi-Fi Reel



Upgrade to DuraSCOPE™!

Hathorn Wi-Fi DuraSCOPE™ reels are designed to work with any Apple or Android mobile device. Stream video inspections directly to your mobile device; record, screen shot, make voice commentary and share video inspections seamlessly. All of these municipal grade Wi-Fi reels are compatible with 18V Milwaukee batteries for the ultimate in portability and are fitted with your choice of DuraCAM™ self-leveling or straight view camera heads all equipped with super bright cool running LEDs for optimal HD picture quality. Butt welded steel frame construction, stainless steel camera heads and your choice of cable size allow you to push further than ever before and remain in the field longer with Hathorn's legendary reliability. Hathorn Wi-Fi DuraSCOPE™ camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a high definition, recordable video inspection every time the camera is used.

Features

- Wi-Fi streaming and recording
- Self-leveling camera heads available
- On-screen footage counter
- 512hz sonde control and reset
- External 18V battery compatibility
- Industry leading HDPE premium cables



HATHORN

RJM Equipment Sales, Inc
800-620-4773 or 360-828-5732
www.rjmcompany.com
sales@rjmcompany.com

DuraSCOPE™

WIFI CAMERA REELS

SPECIFICATIONS

- Compatibility – All portable Apple and Android devices.
- Powered by external Milwaukee™ or comp.18V batteries.
- DuraCAM™ self leveling or straight view camera heads with HD picture quality and auto-iris technology
- 1.00" - 8 cool running LEDs - 8k LUX @ 6"
- 1.23" - 12 cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI

Actual screen shot taken on an iPad from a mini camera in a 3" pipe.



	Catalog#	Camera Head	Self Leveling	Rod Length	Rod Size	Min 90° Elbow	Max. Pipe Well Lit	LBS.	Dimensions
Large	WLR-4168-SL / WLR-4168	1.68"	Avail.	400ft.	1/2"	3"	12"	65lbs.	33"x19"x16"
	WLR-3168-SL / WLR-3168	1.68"	Avail.	300ft.	1/2"	3"	12"	55lbs.	
	WLR-2168-SL / WLR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	45lbs.	
	WLR-4143-SL / WLR-4143	1.43"	Avail.	400.ft	1/2"	3"	10"	65lbs.	
	WLR-3143-SL / WLR-3143	1.43"	Avail.	300.ft	1/2"	3"	10"	55lbs.	
	WLR-2143-SL / WLR-2143	1.43"	Avail.	200.ft	1/2"	3"	10"	45lbs.	
Mid	WMR-2168-SL / WMR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	42lbs.	29"x18"x15"
	WMR-2143-SL / WMR-2143	1.43"	Avail.	200.ft	0.400"	3"	10"		
	WMR-2123-SL / WMR-2123	1.23"	Avail.	200ft.	0.400"	2"	6"		
Mini	WMN-2135	1.35"	No	200ft.	3/8"	1.5"	6"	25-33lbs.	24"x18"x10"
	WMN-2123-SL / WMN-2123	1.23"	Avail.	200ft.	3/8"	2"	6"		
	WMN-2100	1"	No	200ft.	3/8"	1.5"	3"		

* Camera head skirts are included and always recommended to protect camera heads. Roller skirts are recommended options for pipes larger than 8". Find these accessories and spare parts at our website - www.hathorncorp.com



WiFi App available at:



HATHORN

RJM Equipment Sales, Inc
 800-620-4773 or 360-828-5732
www.rjmcompany.com
sales@rjmcompany.com