M2 INSPECTION CAMERA SYSTEM

Proudly designed and manufactured in North America.

Powered by a Milwaukee™ 18V or compatible external battery.





Hathorn M2 systems come standard with a 7.4″ shatter resistant LCD monitor and are compatible with 18V Milwaukee™ batteries for ultimate portability and over 5 hours of runtime on a single charge. All M2s come equipped with 100ft. of premium cable and your choice of DuraCAM™ camera heads, all with cool running super bright LED lights. Trusted by plumbers and contractors all over North America to deliver rugged dependability and portability. Designed and manufactured in North America, with full one-year warranty. The M2 offers a municipal grade product quality with an industry leading feature set.

Upgrade to DuraCAM™!

M2 FEATURES

- 7.4" Impact Resistant Screen
- External 18V battery compatibility
- 512hz sonde control
- Available with Wi-Fi PipeStream™ stream/record



M2INSPECTION CAMERA SYSTEM

Specifications


- DuraCAM[™] straight view camera heads with HD picture quality and auto-iris technology
- 1.23" 12 dimmable cool running LEDs 12k LUX @ 6"
- 1.43" 16 dimmable cool running LEDs 16k LUX @ 6"
- 1.68" 20 dimmable cool running LEDs 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde 512 Hz High-power
- Operating Temperature -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head IPx5 to 60PSI
- Optional wi-fi using free Hathorn app (Apple or Android)
- Powered by 18V Milwaukee or compatible batteries or 12V AC/DC adapter
- Cool running, dimmable high intensity LEDs for longer camera life
- Dimensions 84cm x 48cm x 41cm / 33" x 19" x 16"
- Weight --16kg/ 35lbs

Catalog #	Camera Head	Self Leveling	Rod length	Rod Size	Min 90 Elbow	Max. Pipe well Lit
M2W-1168	1.68"	No	100 ft.	1/2"	3″	12"
M2-1168	1.68"	No	100 ft.	1/2″	3"	12"
M2W-1143	1.43"	No	100 ft.	0.400"	3"	10"
M2-1143	1.43"	No	100 ft.	0.400"	3"	10"

Accesories

Catalog #	Description		
10108 / 10140	Regular Skid for 1.68" / 1.43"		
10137 / 10123	Regular Skid for 1.23" SLC / 1.23" Straight view		
10109	3" Grooved Skid for 1.68" cameras		
10160	3" Grooved Skid for 1.4" Self leveling cameras		
10187	P- Trap Skid for 1.43" cameras		
10162 / 10161	Roller skid for up to 12" pipe (1.68" / 1.43")		













Wi-Fi App available at:







