

REELS				REEL ATTACHMENTS	TAIL PIECES (Loose Wound & Hollow)			CABLES* (see below)	
Part #	Dimensions	Description	Weight	Part #	Part #	Description	Weight	Part #	Dimensions
8SR	8" dia., 8" h	Two-Piece Aluminum Spun Reel	2.6 lbs.	None	None	None	None	25-037 31-037	1/4" up to 37' 5/16" up to 37'
14SR	14" dia., 8" h	Two-Piece Aluminum Spun Reel	8.5 lbs.	None	None	None	None	25-075 31-090 38-090	1/4" up to 75' 5/16" up to 90' 3/8" up to 90'
D1L	14" dia., 9" h	Open Metal Spoke Reel	8.5 lbs.	D3L	None	None	None	25-075 31-060 38-060	1/4" up to 75' 5/16" up to 60' 3/8" up to 60'
D1LE	14" dia., 8" h	Enclosed Metal Spoke Reel	10.5 lbs.	D3S	None	None	None	25-075 31-060 38-060	1/4" up to 75' 5/16" up to 60' 3/8" up to 60'
D1S	16" dia., 8.5" h	Open Metal Spoke Reel	9.5 lbs.	D3L	None	None	None	25-100 31-090 38-090 50-075	1/4" up to 100' 5/16" up to 90' 3/8" up to 90' 1/2" up to 75'
D1SE	16" dia., 8" h	Enclosed Metal Spoke Reel	11.5 lbs.	D3S	None	None	None	25-100 31-090 38-090 50-075	1/4" up to 100' 5/16" up to 90' 3/8" up to 90' 1/2" up to 75'
D1S1	19" dia., 9" h	Open Metal Spoke Reel	21 lbs.	D3L				50-050 62-080 69-050	1/2" up to 50' 5/8" up to 80' 11/16" up to 50'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
D1S1E	19" dia., 8" h	Enclosed Metal Spoke Reel	16.5 lbs.	D3S				50-050 62-080 69-050	1/2" up to 50' 5/8" up to 80' 11/16" up to 50'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
D1J1	21" dia., 9" h	Open Metal Spoke Reel	21.0 lbs.	D3				50-100 62-100 69-090 75-080	1/2" up to 100' 5/8" up to 100' 11/16" up to 90' 3/4" up to 80'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
					CH75-010LW	3/4" x 10'	8 lbs.		
D1J1E	21" dia., 8" h	Enclosed Metal Spoke Reel	24.0 lbs.	D3 D3R D3RJ				50-100 62-100 69-090 75-080	1/2" up to 100' 5/8" up to 100' 11/16" up to 90' 3/4" up to 80'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
					CH75-010LW	3/4" x 10'	8 lbs.		
D1K	26" dia., 9" h	Open Metal Spoke Reel	27.5 lbs.	D3 D3R D3RJ				62-130 69-120 75-110	5/8" up to 130' 11/16" up to 120' 3/4" up to 110'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
					CH75-010LW	3/4" x 10'	8 lbs.		
D1KE	26" dia., 8.5" h	Enclosed Metal Spoke Reel	32.5 lbs.	D3 D3R D3RJ				62-130 69-120 75-110	5/8" up to 130' 11/16" up to 120' 3/4" up to 110'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
					CH75-010LW	3/4" x 10'	8 lbs.		
D1KJ	26" dia., 8.5" h	Open Metal Spoke Reel, Jumbo	28.0 lbs.	D3 D3R D3RJ				62-130 69-120 75-110	5/8" up to 130' 11/16" up to 120' 3/4" up to 110'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
					CH75-010LW	3/4" x 10'	8 lbs.		
26PR	26" dia., 8.5" h	Enclosed Polyethylene Reel	24.7 lbs.	D3 D3R D3RJ				62-130 69-120 75-110	5/8" up to 130' 11/16" up to 120' 3/4" up to 110'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
					CH75-010LW	3/4" x 10'	8 lbs.		
26PRO	26" dia., 8.5" h	Enclosed Polyethylene Reel, Jumbo	26.5 lbs.	D3 D3R D3RJ				62-130 69-120 75-110	5/8" up to 130' 11/16" up to 120' 3/4" up to 110'
					CH62-010LW	5/8" x 10'	7.5 lbs.		
					CH75-010LW	3/4" x 10'	8 lbs.		

**CABLES\***

\* Add **CH** in front of cable part # for Hollow Core  
& Add **LW** after part # if you want it to be Loose Wound

\* Add **CI** in front of cable part # for Inner Core  
& Add **LW** after part # if you want it to be Loose Wound

\* Add **CC** in front of cable part # for Cable-in-Cable (3/4" x 50' or 3/4" x 100' and 11/16" x 50' or 11/16" x 100')

\* Add **OH** in front of cable part # for Oil Tempered Hollow Core

\* Maximum length of cable is not always the recommended length. Custom lengths are available.